SEEK - Bug #1158

create wsdl for ecogrid query level III interfaces

09/26/2003 02:08 PM - Matt Jones

Status:	New		**Start date:**	09/26/2003
Priority:	Normal		**Due date:**	
Assignee:	Peter McCartney		**% Done:**	0%
Category:	ecogrid		**Estimated time:**	0.00 hour
Target version:	Postpone		**Spent time:**	0.00 hour
Bugzilla-Id:	1158			

Description

During Seattle, we redefined the WSDL interfaces for the query operations for
the level III operations.
They now should contain:

Level III

FileHandle open(EcoGridIdentifier, ProxyCertificate)
MimeContent read(FileHandle, Length, ProxyCertificate)
void   seek(FileHandle, Offset)
void   close(FileHandle, ProxyCertificate)

```
MimeContent logicalQuery(EcoGridIdentifier, DataQueryType)
                -- this operation probably needs to be renamed
```

For all of these methods, if "ProxyCertificate" is null, then the method should
be executed anonomously with only the rights of an anonymous user.

Peter agreed to tackle these revisions, and we agreed that these are only
initial thoughts on these more advanced interfaces, and that they would need to
be revised as we gain more experience later.

Related issues:

Is duplicate of SEEK - Bug #1161: create wsdl for ecogrid level III interfaces	**Resolved**	**09/26/2003**

History

#1 - 11/29/2005 11:53 AM - Matt Jones

- Bug 1161 has been marked as a duplicate of this bug. ***

#2 - 03/27/2013 02:16 PM - Redmine Admin

Original Bugzilla ID was 1158