

## Metacat - Bug #196

### Metacat READ function should set mime type

04/09/2001 12:56 PM - Matt Jones

<b>Status:</b>	Resolved	<b>Start date:</b>	04/09/2001
<b>Priority:</b>	Immediate	<b>Due date:</b>	
<b>Assignee:</b>	Jivka Bojilova	<b>% Done:</b>	0%
<b>Category:</b>	metacat	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	Beta2	<b>Spent time:</b>	0.00 hour
<b>Bugzilla-Id:</b>	196		

#### Description

Metacat read function should set the Content-header: to contain the appropriate mime-type for the data being returned. This will allow clients to distinguish metadata downloads (text/xml) from data downloads (application/octet-stream) and allow any object from metacat to be requested using only the accession #.

#### History

##### #1 - 05/02/2001 10:20 AM - Jivka Bojilova

DONE

put MIME type everywhere on return on "read" action. Set metadata returns to "text/html" or "text/xml". Set zip returns to "application/zip". The servlet context guesses the MIME type of the other returned data by its interface getMimeType(filename).

##### #2 - 05/04/2001 03:04 PM - Jivka Bojilova

FIXED

##### #3 - 03/27/2013 02:13 PM - Redmine Admin

Original Bugzilla ID was 196