

## Metacat - Bug #2189

### Refactor skins so returnfield list comes from configuration

09/06/2005 10:12 AM - John Harris

<b>Status:</b>	Resolved	<b>Start date:</b>	09/06/2005
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Matthew Perry	<b>% Done:</b>	0%
<b>Category:</b>	metacat	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	1.7	<b>Spent time:</b>	0.00 hour
<b>Bugzilla-Id:</b>	2189		
<b>Description</b>			
Refactor skins so returnfield list comes from cfg, so then both metacat and mapserver can use this info to generate query, mapserver creates XML resultset then uses XSLT to create result list.			

### History

#### #1 - 07/31/2006 11:52 AM - Matthew Perry

The solution proposed in this bug description:  
web client -> geoserver -> xslt -> html

.. no longer reflects the workflow. The new workflow will be either:

a) web client -> geoserver (do spatial query and gather doc ids) -> metacat servlet

OR

b) web client -> metcat servlet spatial query

Either way, the metacat servlet handles the display and will thus conform to the specifications of the particular skin.

#### #2 - 03/27/2013 02:19 PM - Redmine Admin

Original Bugzilla ID was 2189