# Kepler - Bug #2393

## Need ability to disable 'add port' to actors where not supported

04/03/2006 02:52 PM - Dan Higgins

| | | | |
|---|---|---|---|
| **Status:** | New | **Start date:** | 04/03/2006 |
| **Priority:** | Normal | **Due date:** | |
| **Assignee:** | Matthew Brooke | **% Done:** | 0% |
| **Category:** | actors | **Estimated time:** | 0.00 hour |
| **Target version:** | 3.X.Y | **Spent time:** | 0.00 hour |
| **Bugzilla-Id:** | 2393 | | |

**Description**

Currently one can 'add a port' to any actor even when that actor is not designed to look for new ports. This has confused some new users. It would be useful if there was a way to disable the add port button for individual actors (or enable it for only certain actors!)

**Related issues:**

| | | |
|---|---|---|
| Blocks Kepler - Bug #4333: KeplerLSID AuthNamespace web service | **Resolved** | **08/26/2009** |
| Blocks Kepler - Bug #4219: "Kepler Repositories" should be retrieved from the... | **New** | **07/06/2009** |
| Blocks Kepler - Bug #4314: exception when searching ecogrid | **Resolved** | **08/13/2009** |

### History

**#1 - 03/27/2013 02:20 PM - Redmine Admin**

Original Bugzilla ID was 2393