

Metacat - Bug #30

get dataguide function needed by client

06/21/2000 11:38 AM - Dan Higgins

<b>Status:</b>	Resolved	<b>Start date:</b>	06/21/2000
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Jivka Bojilova	<b>% Done:</b>	0%
<b>Category:</b>	metacat	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	Sep2000	<b>Spent time:</b>	0.00 hour
<b>Bugzilla-Id:</b>	30		
<b>Description</b>			
The client needs to be able to ask the server for a LORE style dataguide for each of the doctypes handled by the server (in order to show a treestructure to guide structured query creation)			

History

#1 - 06/23/2000 12:38 PM - Matt Jones

lowering priority because this is a search feature that requires the user to understand complex queries and something about the semantics of the metadata standards. Will do, but not until more basic infrastructure is completed.

#2 - 07/27/2000 09:02 AM - Jivka Bojilova

assigned to Jivka Bojilova

#3 - 07/28/2000 02:46 PM - Jivka Bojilova

We going to add doctype and docid attr to xml\_index table first in order to be able to retrieve the paths for a given doctype(s), if needed.  
Currently implemented to retrieve all distinct, absolute paths in xml\_index table, ordered in the way they appear in the xml docs.

#4 - 08/08/2000 06:02 PM - Jivka Bojilova

DONE  
Implemented as part of DBUtil class.  
doctype and docid attr are already added to xml\_index table.  
Retrieves all distinct and absolute paths started with '/' for a given doctype (if specified) ordered in the way they appear in the xml docs.  
Are there need to retrive paths for a list of doctypes?

#5 - 09/25/2000 10:28 AM - Jivka Bojilova

It is already DONE and used by dmanclient appl.

#6 - 03/27/2013 02:13 PM - Redmine Admin

Original Bugzilla ID was 30