

FIRST - Bug #3294

Add means for RunWizard class to communicate when it is done

05/13/2008 02:50 AM - Ryan McFall

Status:	Resolved	Start date:	05/13/2008
Priority:	Normal	Due date:	
Assignee:	Ryan McFall	% Done:	0%
Category:	parser	Estimated time:	0.00 hour
Target version:	Unspecified	Spent time:	0.00 hour
Bugzilla-Id:	3294		

Description

Three options:

Add a getFrame method

Add delegate methods to add listeners to the frame

Make constructor take a wizard event listener as a parameter to constructor, and add it as a listener automatically.

If we do getFrame() then we can also access the wizard data object at that point. This complicates the interface to RunWizard.

I'm leaning toward the constructor method, along with an explicit delegated getWizardData method.

History

#1 - 05/13/2008 10:00 AM - ben leinfelder

I'm not a huge fan of constructors with lots of arguments and prefer that methods exist that do the various bits and pieces:

```
RunWizard.addWizardEventListener(listener)
```

```
RunWizard.getWizardData()
```

would satisfy me.

#2 - 05/13/2008 11:47 AM - Ryan McFall

You got it, they're there!

#3 - 03/27/2013 02:22 PM - Redmine Admin

Original Bugzilla ID was 3294