

## Kepler - Bug #3967

### Unable to run java -jar kepler-trunk.jar with -nogui -nocache -runwf fullworkflowpath options

04/08/2009 01:23 PM - Madhusudan Gujral

<b>Status:</b>	Resolved	<b>Start date:</b>	04/08/2009
<b>Priority:</b>	Immediate	<b>Due date:</b>	
<b>Assignee:</b>	Chad Berkley	<b>% Done:</b>	0%
<b>Category:</b>	general	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	2.0.0	<b>Spent time:</b>	0.00 hour
<b>Bugzilla-Id:</b>	3967		
<b>Description</b>			
I am unable to run  java -jar kepler-trunk.jar -nogui -nocache -runwf fullworkflowpath  arguments are completely ignored.  I create kepler-trunk.jar by running ant package target.			
<b>Related issues:</b>			
Blocked by Kepler - Bug #3949: Get the installer working with the new build s...			<b>Resolved</b> <b>04/06/2009</b>

#### History

##### #1 - 04/22/2009 03:33 PM - Chad Berkley

check that all command line arguments are passed to the execution scripts.

##### #2 - 04/24/2009 04:46 PM - Chad Berkley

There are now two ways to do this. On the installed version of kepler, you can use the kepler.sh or kepler.bat files to pass whatever arguments you want. On the svn version of kepler, use the command 'ant startupScript' to generate the scripts in the root kepler directory. Those scripts can be passed arguments.

In addition, this will also create a kepler.jar file in the root that can execute kepler with 'java -jar kepler.jar'. Please see the startup scripts for specific syntax.

##### #3 - 03/27/2013 02:25 PM - Redmine Admin

Original Bugzilla ID was 3967