## Metacat - Bug #452

## Configure ssl in dev and ecoinfo

04/02/2002 11:00 AM - Jing Tao

Status: Resolved Start date: 04/02/2002 **Priority:** Normal Due date: Assignee: % Done: 0% Jing Tao Category: **Estimated time:** 0.00 hour metacat Target version: 1.1 Spent time: 0.00 hour

# Bugzilla-ld: Description

We already configured ssl in local machine (Tomcat standalone). Now we need to configure dev and ecoinfo. But in these machines, apache is the web server and need more configuration than tomcat standalone.

#### History

#### #1 - 04/02/2002 09:17 PM - Jing Tao

1. Enable Apache over ssl:

In /etc/httpd/conf/httpd.cof file, comment every <ifdef have\_ssl>

452

#### 2. Restart Apache:

/etc/init.d/httpd stop

/etc/init.d/httpd start

#### 3. Download and install JSSE:

Download JSSE package from java.sun.com and unzip it. Copy the three files -jcert.jar, jnet.jar and jsse.jar in Jsse\_home/lib to \$Java\_home/jre/lib/ext

#### 4. Edit file \$Tomcat\_home/conf/server.xml

Uncomment the part about https and make them look like:

<http10Connector port="8443"

secure="true"

keystore="/home/tao/.keystore"

keypass="123456"

clientAuth="false"

SSLImplementation="org.apache.tomcat.util.net.JSSEImplementation" />

Don't comment the Http10Connector for port 8080. It will be use to catch systle sheet and other things.

#### 5. Edit the build.xml in metacat.

Add a property named systemidserver, its value="http://dev.nceas.ucsb.edu"

- 6. Install Metacat again from scratch (include "ant dtdsql")
- 7. Stop and start tomcat.

Now, dev can support ssl.

### #2 - 04/03/2002 10:42 AM - Jing Tao

6.b Put the public of Apache into default keystore of Java:

If Metacat cmmiunicate to Apache server by https, for example to call a sytle sheet, Apache pulbic key should be import into a keystore. Because Metacat didn't specify the keystore, the public key should be import the default store: \$java\_home/jre/lib/security/cacerts. The import can be finished by keytool commnad. The location of public key of Apache server can found in /etc/httpd/conf/httpd.cof file.

Moreover, when Apache as web server and Tomcat as servlet container, we only need to distribute the public of Apache. Actually, Tomcat don't need any private key or public key.

#### #3 - 04/18/2002 03:37 PM - Jing Tao

03/13/2024 1/2

Testing between dev and my local amchine, the replication work well through

## #4 - 03/27/2013 02:14 PM - Redmine Admin

Original Bugzilla ID was 452

03/13/2024 2/2