

Metacat - Bug #466

Create a JUnit class for Metacat action

04/09/2002 01:12 PM - Jing Tao

Status:	Resolved	Start date:	04/09/2002
Priority:	Normal	Due date:	
Assignee:	Jing Tao	% Done:	0%
Category:	metacat	Estimated time:	0.00 hour
Target version:	1.2	Spent time:	0.00 hour
Bugzilla-Id:	466		

Description

We need a JUnit class for testing the action of metacat. These actions insert, update, delete, with valid, invalid, wf, and non-wf docs, login, and logout ...

When it is done, we will be very convenience to test our Metacat.

History

#1 - 05/22/2002 01:19 PM - Jing Tao

Test cases for successful and failed login as NCEAS, PISCO and LTER ladp users were created.

Test cases for inserting valid, invalid, wf and non-wf xml documents were created.

Test cases for update, delete, read (for xml, html and zip qformat) and logout action were created too.

These test case were created in edu.ucsb.nceas.metacatjunittests.MetaCatServletTest class and run it by type "ant test"

In order to testing insert data file. We need httpclient.jar and itislib.jar file. We create another package for testing insert data file (including the above test cases too). It is edu.ucsb.nceas.metacatunitnettests and in the build.xml file two another targets were created. One is "gethttpclient". This target will download morpho from cvs and run ant to get httpclient.jar. After running gethttpclient, then we can run another target "nettest". In this test, insert data file will be executed.

This is basic test. And we will put more there.

#2 - 03/27/2013 02:14 PM - Redmine Admin

Original Bugzilla ID was 466