

Metacat - Bug #478

Security hole in Metacat for data file.

04/30/2002 09:10 AM - Jing Tao

<b>Status:</b>	Resolved	<b>Start date:</b>	04/30/2002
<b>Priority:</b>	Immediate	<b>Due date:</b>	
<b>Assignee:</b>	Jing Tao	<b>% Done:</b>	0%
<b>Category:</b>	metacat	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	1.2	<b>Spent time:</b>	0.00 hour
<b>Bugzilla-Id:</b>	478		
<b>Description</b> In metacat, data files are put into the data directory in the same directory as the servlet context. So one can do a directory listing of all of the data that metacat is storing.we need to move that directory somewhere not web accessible.			

History

#1 - 05/11/2002 05:40 PM - Jing Tao

In build.xml, metacat administrator can specify a absolute path for storing data file. The property name is datafilepath. During the installation, Metacat can automaticlly create this directory.

Here is the testing:

Using morpho, new data file can be create in data file directroy. The the data file can be access by read and export.

The data file can be force and delt T replication too.

An old data file was move to the new data directory. The file can be read and export too.

#2 - 03/27/2013 02:14 PM - Redmine Admin

Original Bugzilla ID was 478