

Kepler - Bug #4782

configuration files do not load with non en_US locale

02/09/2010 11:00 AM - Daniel Crawl

Status:	Resolved	Start date:	02/09/2010
Priority:	Normal	Due date:	
Assignee:	Chad Berkley	% Done:	0%
Category:	general	Estimated time:	0.00 hour
Target version:	2.0.0	Spent time:	0.00 hour
Bugzilla-Id:	4782		

Description

If the locale is not set to en_US, the configuration files do not load. I can reproduce this on my mac by:

```
export LC_ALL=fi_FI
ant run-only
```

If modules.txt contains the kepler suite, the menu bar does not load; if it contains wrp, then I get the following exception:

```
[run] java.lang.NullPointerException
      [run]    at org.kepler.configuration.ConfigurationManager.getProperty(ConfigurationManager.java:308)
      [run]    at org.kepler.module.tagging.Initialize.addTagManagerMenuItem(Initialize.java:94)
      [run]    at org.kepler.module.tagging.Initialize.initializeModule(Initialize.java:56)
      [run]    at org.kepler.Kepler._initializeModules(Kepler.java:460)
      [run]    at org.kepler.Kepler.initialize(Kepler.java:347)
      [run]    at org.kepler.Kepler.parseArgsAndRun(Kepler.java:233)
      [run]    at org.kepler.Kepler.main(Kepler.java:170)
```

History

#1 - 02/09/2010 12:06 PM - Chad Berkley

added a method to use a default locale tagged file if the currently set locale is not available.

#2 - 02/09/2010 01:55 PM - Daniel Crawl

fixed in r23033. Thanks Chad!

#3 - 03/27/2013 02:28 PM - Redmine Admin

Original Bugzilla ID was 4782