

Kepler - Bug #5279

HSQL databases use default account

01/26/2011 11:14 AM - Daniel Crawl

Status:	Resolved	Start date:	01/26/2011
Priority:	Normal	Due date:	
Assignee:	Daniel Crawl	% Done:	0%
Category:	core	Estimated time:	0.00 hour
Target version:	2.4.0	Spent time:	0.00 hour
Bugzilla-Id:	5279		
Description			
The HSQL databases should not use the default account name and password.			
Related issues:			
Is duplicate of Kepler - Bug #5463: Provide security for Kepler databases			Resolved 08/15/2011

History

#2 - 06/15/2012 11:27 AM - Ilkay Altintas

Maybe generate a new username or password at runtime and save it under kepler data. Dan will design this.

#3 - 09/21/2012 02:38 PM - Daniel Crawl

I've updated org.kepler.util.sql.HSQL to generate a password for the HSQL databases. The password is stored in a text file in the same directory as the database files.

I changed the location of the Kepler cache to .kepler/cache-2.4 and the ports used for HSQL server mode so that these updates are compatible with previous Kepler versions.

I will update <https://kepler-project.org/developers/reference/accessing-hsql/> with the new ports and access information.

#4 - 03/27/2013 02:29 PM - Redmine Admin

Original Bugzilla ID was 5279