

## Kepler - Bug #5463

### Provide security for Kepler databases

08/15/2011 02:08 PM - Derik Barseghian

<b>Status:</b>	Resolved	<b>Start date:</b>	08/15/2011
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Daniel Crawl	<b>% Done:</b>	0%
<b>Category:</b>	core	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	2.4.0	<b>Spent time:</b>	0.00 hour
<b>Bugzilla-Id:</b>	5463		

#### Description

By default, Kepler keeps certain data in hsql dbs, run as servers. If someone knows your ip, your servers are up, and you're not running a firewall, they can connect and delete your data.

The hsql 2.0 docs have this section:

[http://hsqldb.org/doc/2.0/guide/listeners-chapt.html#listeners\\_acl-sect](http://hsqldb.org/doc/2.0/guide/listeners-chapt.html#listeners_acl-sect)

#### Related issues:

Has duplicate Kepler - Bug #5279: HSQL databases use default account

**Resolved**

**01/26/2011**

#### History

**#1 - 08/15/2011 02:18 PM - Derik Barseghian**

duplicate

**#2 - 03/27/2013 02:30 PM - Redmine Admin**

Original Bugzilla ID was 5463