

Metacat - Bug #5718

SANParks GIS download returns empty files

09/25/2012 07:25 AM - ben leinfelder

Status:	Resolved	Start date:	09/25/2012
Priority:	Normal	Due date:	
Assignee:	ben leinfelder	% Done:	0%
Category:	metacat	Estimated time:	0.00 hour
Target version:	2.0.5	Spent time:	0.00 hour
Bugzilla-Id:	5718		

Description

The files are intact on the server and can be downloaded manually using the metacat?action=read urls, but the special skin for downloading them does not work.
Looks at the "client view helper" code I can see that it is improperly constructing value=key pairs when calling the Metacat servlet. This has been in the code for years, so I'm not sure how it was ever working!

History

#1 - 09/25/2012 07:29 AM - ben leinfelder

example of the MetacatClient request that was constructed:

knb 20120925-16:13:58: [DEBUG]: >>

```
"zip=qformat&boundary_kruger.shp=judith_kruger.56.1&read=action&judith_kruger.56.1=docid&boundary_kruger.prj=judith_kruger.59.1&boundary_kruger.dbf=judith_kruger.57.1&judith_kruger.57.1=docid&boundary_kruger.xml=judith_kruger.55.1&judith_kruger.58.1=docid&judith_kruger.59.1=docid&boundary_kruger.sbx=judith_kruger.58.1&judith_kruger.55.1=docid" [org.apache.http.wire]
```

#2 - 09/25/2012 09:50 AM - ben leinfelder

will be included in the 2.0.5 Metacat release.

#3 - 03/27/2013 02:31 PM - Redmine Admin

Original Bugzilla ID was 5718