

Kepler - Bug #6165

The names of instances of the Stop actor do not display in Mac OSX.

10/21/2013 05:48 PM - Christopher Brooks

Status:	Resolved	Start date:	10/21/2013
Priority:	Low	Due date:	
Assignee:	Daniel Crawl	% Done:	0%
Category:	interface	Estimated time:	2.00 hours
Target version:	2.5.0	Spent time:	0.00 hour
Bugzilla-Id:			
Description			
On Kepler-users, Kenneth Jones wrote:			
The names of instances of the Stop actor do not display in Mac OSX. Let me know if you need more info.			
Indeed, dragging in the Stop Actor results in icons without instance names			

History

#1 - 10/21/2013 06:10 PM - Christopher Brooks

Edward wrote:

BTW, the reason for this is that the icon for the Stop actor in Ptolemy says it all. Unfortunately, the icon in Kepler says nothing about what the actor does. The constructor for the Stop actor includes this:

```
// Hide the name because the name is in the icon.
    _hideName = new SingletonParameter(this, "_hideName");
    _hideName.setToken(BooleanToken.TRUE);
    _hideName.setVisibility(Settable.EXPERT);
```

I suggest that in the Kepler library, the Stop actor should include something like:

```
&lt;property name="_hideName" value="false"/&gt;
```

#2 - 12/23/2014 03:24 PM - Daniel Crawl

- Target version changed from 2.4.0 to 2.5.0
- Assignee changed from Derik Barseghian to Daniel Crawl
- Status changed from New to Resolved

The library metadata for Stop has been updated as Edward suggested.

Files

StopInstanceNameMissing.png	18.6 KB	10/22/2013	Christopher Brooks
-----------------------------	---------	------------	--------------------