

Metacat - Bug #7187

Set file names correctly when reading objects from Metacat

05/10/2017 08:05 AM - Chris Jones

Status:	Resolved	Start date:	05/10/2017
Priority:	Normal	Due date:	
Assignee:	Chris Jones	% Done:	0%
Category:	metacat	Estimated time:	0.00 hour
Target version:	2.8.3	Spent time:	0.00 hour
Bugzilla-Id:			
Description			
We now store file names in SystemMetadata.fileName. In MetacatHandler.readFromMetacat(), we are currently generating a file name based on the docid, and setting it into the Content-Disposition header. Change generateOutputName() to use SystemMetadata.fileName when it's available, and fall back to generating a file name.			

History

#1 - 05/10/2017 08:08 AM - Chris Jones
- Target version changed from 2.8.3 to 2.9.0

#2 - 05/10/2017 08:15 AM - Chris Jones
- Status changed from New to In Progress

I've modified generateOutputName to use SystemMetadata.fileName when it's available. We'll need to test this in a 2.9.0 deployment.

#3 - 05/22/2017 10:56 AM - Jing Tao
- Target version changed from 2.9.0 to 2.8.3

#4 - 05/23/2017 03:32 PM - Jing Tao
- Status changed from In Progress to Resolved

Tested it and it worked.

#5 - 05/30/2017 11:42 AM - Chris Jones
- Target version changed from 2.8.3 to 2.8.4

#6 - 05/30/2017 12:39 PM - Jing Tao
- Target version changed from 2.8.4 to 2.8.3

It is in the 2.8.3 release.